





Accessories / Zubehör / Accessoires:

<p>Set (4) rubber blocks Set (4) Gummi-Blöcke Set (4) rubber blokken</p>  <p>BA-RB80 (4x 160x120x80mm) BA-RB120 (4x 160x120x120mm)</p>	<p>Set (2) Closed build-in cassette Set (2) Geschlossene Einbaukassette Set (2) Gesloten inbouw cassette Galvanized Galvanisiert Gegalvaniseerd</p>  <p>ASG4008: BICCG4006/1600/260 ASG4008L: BICCG4006/2100/290</p>	
<p>Set crossbeams to pick up 4WD vehicles Set Traversen auf 4WD Fahrzeuge abholen Set crossbeams voor opname 4WD voertuigen</p>	 <p>BA-A3/TRAV</p>	

Technical specifications / Technische Spezifikationen / Technische specificaties:

			ASG4006L	
Capacity	Tragfähigkeit	Hefvermogen	4.000 kg	
Lifting time	Hebezeit	Heftijd	35 s	
Descent time	Absenzeit	Daaltijd	40 s	
Noise level	Lärmpegel	Geluidsniveau	<74 dB (A) / 1 m	
Working temp.	Arbeitstemp.	Werktemp.	-10 °C / +50 °C	
Motor power	Motorleistung	Motorvermogen	2,2 kW	
Electr. Supply	Anschlußwert	Aansl. waarde	230/400V / 50Hz/ 3 Ph	
Color	Farbe	Kleur	RAL 5015	
Working envir.	Arbeitsumgeb.	Werkomgeving	Indoor/Drinnen/Binnen	

<p>Packing/Verpackung/Verpakking:</p>  <p>730 kg</p>	<p>Container transport:</p>  <p>20 ft. = 9 pieces/Stück/stuks</p>
---	---